

CooVox-U20

CooVox-U20 is a stylish, compact yet full-featured mini IPPBX system designed for small and micro firms/SOHOs. It is suitable for companies under 30 employees and has all the necessary functionality to fulfill their daily telephony needs.

CooVox-U20 comes equipped with 2 analog ports and optionally a GSM interface, allowing companies the option to deliver inbound/outbound phone calls over PSTN/GSM/SIP Trunk/IMS. With the U20, it is possible to deploy up to 2 EX16S expansion boxes for up to 32 legacy phone deployment. This low-cost IPPBX packs a powerful punch, with a rich feature set that can rival the most expensive of Enterprise solutions in today's market place.



Advantages

✓ Quick Setup Wizard

Quick Setup Wizard allows speedy initial configuration of the U20 system. The wizard includes all essential configuration steps in an easy to use and intuitive web based interface.

✓ Endpoints Provisioning

Quick and simple deployment of endpoint devices using PNP and Quick Register Code. CooCall APP can be provisioned by scanning a QR code.

✓ Extension Web Portal (WebRTC Integrated)

Thanks to the extension web portal, you can now Playback voicemail/recordings online, make/receive phone calls, click to dial, incoming call pop-up, send fax. All of this from within your web browser without installing any plugins.

√ SIP Proxy Service

No fixed public IP, third-party DDNS services and VPN router required. Remote extension and remote branch office phone system integration have never been easier!

✓ Billing

With built-in billing system, no third-party billing software required. Prepaid/postpaid billing, billing credit, flexible billing rates and billing statistics features are all supported.

√ Web Conference Manager

By using web conference manager, it will be much easier for you to start and manage a conference from the Web interface. Invite participants, mute/unmute participants, kick out participants can be done by a few mouse clicks.

Hardware Specifications

Items	Specifications
Telephony Interfaces	2xRJ11 Interfaces (FXO/FXS); 1xGSM (Optional)
CPU	1GHz ARMv7 Processor
SDRAM	512MB DDR3
Storage	16GB SD Card
USB (Extended Storage Supported)	1 (Supported File System: FAT16,FAT32,EXTFAT,NTFS,EXT3,EXT4)
Ethernet Interface	WAN, LAN (10/100Mbps)
Power	DC 12V, 1A
Dimension	170x116x30 (Desktop based)

Software Specifications

System Capacity	 ✓ 32 Extensions ✓ Unlimited IVR Levels ✓ 15 Simultaneous Calls ✓ 20 SIP/IMS Trunks (Max) ✓ 500000 CDR History ✓ 150hrs Recording/Voicemail (Internal Storage) ✓ 1 or 2 EX16S Deployment (Recommended) ✓ 15 Paging Members 	
Protocols & Codecs	 ✓ SIP(RFC3261), IAX2 ✓ DTMF(RFC4733, SIPINFO, In-Band) ✓ Transport Protocols: UDP, TCP, TLS, SRTP ✓ Network Protocols: IPv4, IPv6, VLAN, DHCP, PPPoE, NTP, SNTP, TFTP, SSH, HTTPS, LDAP ✓ Video Codecs: VP8, H.264, H.263+, H.263, H.261 ✓ Audio Codecs: Opus, G.722, G.711(a-law, u-law), G.729, G.726, GSM, SPEEX, AMR, AMR-WB 	
Telephony Features	 ✓ Call Queue ✓ IVR (Multi-layer) ✓ DISA ✓ Time Conditions ✓ Ring Group ✓ Caller ID ✓ Smart DID ✓ Paging & Intercom ✓ Call Forward ✓ Call Spy ✓ Blacklist ✓ One Number Stations ✓ Call Transfer ✓ Video Call ✓ Voicemail ✓ Music On Ringback ✓ Call Pickup ✓ 3-way Calling ✓ Wakeup Call ✓ Distinctive Ringtone ✓ Call Parking ✓ Conference Call ✓ PIN Code ✓ Auto Call Recording ✓ Call Waiting ✓ Follow Me ✓ Do Not Disturb ✓ One Touch Recording ✓ Speed Dial ✓ Call Back ✓ Switch Call ✓ Call Detailed Records (CDR) 	
Feature Highlights	 ✓ Quick Installation Guide ✓ SIP Proxy (NAT Traversal) ✓ Softphone APP Auto Provisioning (QR Code Scan) ✓ Voicemail to Email ✓ IP Phone Auto Provisioning (PNP, Quick Register Code) ✓ Fax to Email ✓ LDAP Phonebook Auto Configure (H81, H83) ✓ Multilingual Web UI ✓ EX16S Auto Provisioning ✓ Multilingual Voice Prompts 	
Multi-level User Administration	 ✓ Admin user: All Privileges. ✓ Operator user: Extensions, faxes, CDR, recordings, etc. ✓ Extension user: WebRTC, recordings, voicemails, call logs, etc. 	
Security	 ✓ Firewall based on iptables ✓ Intrusion auto detection and prevention ✓ Geo-IP (Security policy based on IP address geographical location) ✓ IP Black/White List ✓ Extension Permit IF	
Network Features	 ✓ Network (WAN): Static IP, DHCP, PPPoE ✓ VPN: PPTP, OpenVPN, IPSec, L2TP ✓ (Server and Client) ✓ Static Routing ✓ DDNS (Dynamic Domain Name Server) ✓ VLAN (WAN & LAN Interface) ✓ Virtual IP ✓ Local Domain Name Services ✓ DHCP (Server and Client) ✓ SIP Proxy (NAT Traversal) 	

Add: 16F, D5, Tianfu Software Park, Chengdu, China Tel: +86(28)85337096

Email: zycoo@zycoo.com Website: www.zycoo.com

