



# Fanvil X7C Enterprise IP Phone

With a modern, clear design, Fanvil X7C is a high-end enterprise IP phone for business users who need immediate access to all of their important information. In addition to a 5-inch high-resolution color screen, the telephone also features 20 SIP lines, HD audio with Opus support, up to 60 DSS keys (12 physical), Built-in Bluetooth, Wi-Fi connectivity and more!

## Highlights

- ☑ 20 SIP lines
- ☑ 5" high-resolution color display
- ☑ HD audio on speakerphone and handset
- ☑ Up to 60 DSS keys entries available (12 physical)
- ☑ Built-in Bluetooth for connecting Bluetooth headset
- ☑ Wi-Fi connectivity (via Wi-Fi dongle)
- ☑ Video codec H.264 support for receiving video calls
- ☑ Stand with 2 adjustable angles of 40 and 50 degrees
- ☑ Dual Gigabit ports, integrated PoE
- ☑ Compatible with major platforms: 3CX, Avaya, Asterisk, Broadsoft, Metaswitch, Elastix etc.



Model	Screen	Network	PoE	Power adapter
X7C	5.0" color-screen	10/100/1000Mbps	✓	—

## Generic

- 20 SIP Lines
- HD Voice
- Support receiving Video call
- POE Enabled
- 5 Inch Color LCD Screen
- Handset / Hands-free / Headset mode
- Intelligent DSS Keys
- Optional External Power Supply

## Video

- Video codec: H.264
- Video call resolution: QCIF / CIF / VGA

## Call Features

- Call out / Answer / Reject
- Mute / Unmute (microphone)
- Call Hold / Resume
- Call Waiting
- Intercom
- Caller ID Display
- Speed Dial
- Anonymous Call (Hide Caller ID)
- Call Forwarding (Always/Busy/No Answer)
- Call Transfer (Attended/Unattended)
- Call Parking/Pick-up (depending on server)
- Redial
- Do-Not-Disturb
- Auto-Answering
- Voice Message (on server)
- 3-way Conference
- Hot Line
- Hot desking

## Phone Features

- Local Phonebook (2000 entries)
- Remote Phonebook (XML/LDAP, 2000 entries)
- Call logs (in/out/missed, 1000 entries)
- Black/White List Call Filtering
- Screen saver
- Voice Message Waiting Indication (VMWI)
- Programmable DSS/Soft keys
- Network Time Synchronization
- Built-in Bluetooth 2.1: Support Bluetooth headset
- Support Wi-Fi Dongle
- Support Plantronics wireless headset (Through Plantronics APD-80 EHS Cable)
- Support Jabra wireless headset (Through Fanvil EHS20 EHS Cable)
- Support Recording (Through Flash Drive or Server Recording)
- Action URL / Active URI
- uaCSTA

## Audio

- HD Voice Microphone/Speaker (Handset/Hands-free, 0 ~ 7KHz Frequency Response)
- HAC handset
- Wideband ADC/DAC 16KHz Sampling
- Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB, AMR, iLBC
- Wideband CODEC: G.722, AMR-WB, Opus
- Full-duplex Acoustic Echo Canceller (AEC)
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

## Networking

- Physical: 10/100/1000 Mbps Ethernet, dual bridged port for PC bypass
- IP Mode: IPv4/IPv6/IPv4&IPv6
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- LLDP
- QoS
- RTPC-XR(RFC3611), VQ-RTCPXR(RFC6035)

## Deployment & Maintenance

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/ SIP PNP/TR-069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Phonebook Import/Export
- Firmware Upgrade
- Syslog

## Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- IPv6
- LLDP
- PPPoE
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR-069

## Physical Specifications

- Main LCD x1: 5.0 inch (800x480) color-screen LCD
- Keypad: 43 keys, including
  - 4 Soft-keys
  - 12 DSS Keys with tri-color LED
  - 1 Page-Switch (PS) key
  - 5 Function keys (Hold, MWI, Mute, Headset, Redial)
  - 4 Navigation keys
  - 1 OK key
  - 1 Return key
  - 12 Standard Phone Digits keys
  - 2 Volume Control keys, Up/Down
  - 1 Hands-free key
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- 1.5M CAT5 Ethernet Cable x1
- Back Rack x1
- RJ9 Port x2: Handset x1, Headset x1
- RJ45 Port x2: Network x1, PC x1 (Bridged to Network)
- USB2.0 Port x1: Standard A, Connect with Wi-Fi USB dongle or Flash Driver
- DC Power Input: 5V/2A
- Power Consumption (POE): 2.6~9W
- Power Consumption (Adapter): 2.4~8W
- Working Temperature: 0~40°C
- Working Humidity: 10~95%
- Installation: Desktop Stand
- Color: Black
- Device Dimensions
  - Desktop Stand (angles 1): 268x185x189mm
  - Desktop Stand (angles 2): 268x201x168mm
- Gift Box Dimensions: 342x271x63mm
- Outer CTN Dimensions: 570x340x365mm (10 PCS)

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.

For more information, please visit : [www.fanvil.com](http://www.fanvil.com)

## Compatibility List:



[www.fanvil.com](http://www.fanvil.com)

Add: 4F, Block A, Building 1#, GaoXinQi Hi-Tech Park (Phase-II), 67th District, Bao'An, Shenzhen, China 518101

Tel: +86-755-2640-2199 Fax: +86-755-2640-2618 Email: [sales@fanvil.com](mailto:sales@fanvil.com)

