SANG

SBC Series designed to provide SMBs, enterprises and service providers with unbeatable VoIP protection

Why You Need an SBC

Businesses connecting their infrastructure to a SIP Trunk, or VoIP connection will primarily use an SBC to protect their VoIP network, as well as for interoperability, transcoding, and failover of their voice network.

How Does It Work

An SBC is a device that sits between your internet connection and corporate network and analyses all the VoIP traffic that passes through. It is designed with security features to detect malicious VoIP traffic and automatically take action to save your network.



Business Network

When Would You Use an SBC

- SIP Trunking An SBC will prevent hackers from finding your IP address and attempt to initiate malicious activity
- Hosted Phone Service The service provider will have an SBC to protect their network, but your network also needs an SBC to protect your network
 Remote Workers Lock down your network and securely connect remote workers to your corporate network

Enhance Your Security to Protect Your VolP Network

Often times, businesses will forget the importance of an SBC when switching from their legacy phone system to VoIP and simply use their existing firewall for protection, and make a huge mistake! Many ports in the firewall need to be opened for VoIP to function which gives hackers a wide open door into your network and compromise your business. The other pitfall of using your existing firewall, instead of an SBC, is that phone calls may not connect or there will be audio issues.



Technical Specifications

Capacities

- Max call / sessions
- 4000 Sangoma Carrier SBC
- 1000 Virtual Machine (VM) SBC
- 250 Enterprise SBC
- 30 SMB SBC
- Unlimited SIP trunks
- Max. 120 TDM-SIP calls/sessions
 * Applicable only to Enterprise SBC
- Full security (SRTP / TLS)
- Full transcoding capability (excludes SMB SBC)

Media Capabilities

- Voice, Video, FAX, IM and Presence support
- Full RTP transcoding (G.711, G.722, G.729, G.726, G.723.1, iLBC, AMR, G.722.1)
 *Only with hardware transcoding option
 T.38 Fax Relay

Networking

- 10/100/1000 BaseT Ethernet ports
- 6x Sangoma Carrier SBC
- 3x Enterprise SBC
- 4x SMB SBC
- IPV4, IPV6
- VLAN support

Licensing

Field upgradeable in 5/10 call increments (SMB)Field upgradeable in 25/50/100/250 call increments

Security

- DDoS / DoS attack protection
- · Media security with SRTP
- IPSec encryption
- · IP firewall with port forwarding
- · Call security with TLS / SRTP
- Two-stage authentication

VolP

- SIP 2.0 compliant
- SIP intrusion prevention
- SIP trunking and remote working
- SIP registration pass-thru
- SIP malformed packet protection
- Topology hiding
- ENUM routing
- SIP request rate limiting
- SIP registration scan attack detection
- SIP friendly load limitation
- SIP header normalization
- Advanced NAT traversal capabilities

Debugging

- Dedicated Browser interface for capturing full RTP media and signaling information
- Onboard browser-based PCAP tracing, signaling and media – wireshark compatible
- Large onboard storage capacity for long term tracing

Session and Monitoring

- Multiple session routing options
- RTCP statistics reports
- QoS (ToS or DSCP)
- RADIUS CDR and authentication
- QoS monitoring and reporting

High Availability / Redundancy

• 1:1 active / standby two-box redundancy to guarantee business continuity

Call Control

- Least cost routing
- Multiple call access control options
- Rate limiting: Call and registration
- Endpoint authentication
- Dynamic load balancing and call routing
- Advanced XML routing engine
- Intelligent media anchoring / release
- Media bandwidth policy

Management

- Easy to use web interface
- · Real-time monitoring and debugging
- HTTP XML-based CDR
- TR-069 for remote provisioning
- REST based interface to remotely configure SBCs

Telephony Interface (Enterprise SBC)

- Up to 4 E1/T1s (with A101DE/A102DE/A104DE card)
- Echo cancellation up to 128ms tail
- Primary rate ISDN, configurable NT/TE
- T1: 0.931, NI2, 4ESS, 5ESS, DMS-100
- E1: Q.931, ETSI



Hardware Specifications & Minimum Requirements

SMB SBC

- Power: External universal AC/DC power brick
- Dimensions: 127mm (W) x 127mm (D) x 50mm (H)
- Weight: .68kgs (1.5lbs)

Enterprise SBC

- Power: 60W universal internal power supply
- Dimensions: 430mm (W) \times 305mm (D) \times 45mm (H)
- Weight: 7.25kgs (16lbs)
- Mounting clips included

Sangoma Carrier SBC

- Power: Dual internal 100~240V power supply
- Dimensions: 430mm (W) x 520mm (D) x 44.5mm (H)
- Weight: 6.35kgs (14lbs)
- 19 inch rackmount brackets included

VM SBC:

- Hypervisor: VMware, ESX, Linux KVM, Microsoft Hyper-V, Oracle Virtualbox
- · Virtual Network Interfaces: minimum 1 (2 preferred)

SANG(*

- Virtual Cores: 1-4
- · Memory: 2GB
- Disk Space: 20GB

100 Renfrew Drive, Suite 100, Markham ON L3R 9R6 Canada * +1 (256) 428-6000 or 1 (877) 344 4861 (toll free in N. America)